

Datasheet

EPT-2330

Charging voltage	400-600 V DC regulated
max. Output power	max. 3 kW
Connector Plug	Europlug with 1,5 m cable / 230 V (max. backup 16 A)
Inverter	MC4 Plug/Socket
Protecting class	IP20
Cooling system	active cooling
Mounting distances	min. spacing 300 mm all sides
Mounting type	in House installation, Wallmounting with screws, dowels, (mounting material is not included)
Dimension L x W x D	340 x 440 x 230
Net weight	15 kg
Net weight range	10 bis 35 °C (try)



EPT-2360

Charging voltage	400-600 V DC regulated
max. Output power	max. 6 kW
Connector Plug	CEE Wall device plug 5-pin 16 A / 400 V (max. backup 16 A)
Inverter	MC4 Plug/Socket
Protecting class	IP20
Cooling system	active cooling
Mounting distances	min. spacing 300 mm all sides
Mounting type	in House installation, Wallmounting with screws, dowels, (mounting material is not included)
Dimension L x W x D	640 x 440 x 230
Net weight	27 kg
Net weight range	10 bis 35 °C (try)



EPT-23120

Charging voltage	400-600 V DC regulated
max. Output power	max. 12 kW
Connector Plug	CEE Wall device 5-pin 32 A / 400 V (max. backup 32 A)
Inverter	MC4 Plug/Socket
Protecting class	IP20
Cooling system	active cooling
Mounting distances	min. spacing 300 mm all sides
Mounting type	in House installation, Wallmounting with screws, dowels, (mounting material is not included)
Dimension L x W x D	650 x 650 x 400
Net weight	55 kg
Net weight range	10 bis 35 °C (try)



